

# PDFBraindumps



Latest Pdf Braindumps	Top Certifications	Top Vendors		
<ul style="list-style-type: none"><li>▶ LRP-614</li><li>▶ BCABA</li><li>▶ JN0-740</li><li>▶ 250-405</li><li>▶ DS-200</li><li>▶ SDM_2002001040</li><li>▶ ST0-250</li><li>▶ H12-221</li><li>▶ M2180-716</li></ul>	<ul style="list-style-type: none"><li>▶ ISEB Certification</li><li>▶ OCE</li><li>▶ NVIDIA Certifications</li><li>▶ Network+</li><li>▶ IBM Certified Integrat</li><li>▶ CCDH</li><li>▶ IBM Certified Advanc</li><li>▶ eserver Certified Spe</li><li>▶ SAP-Certifications</li><li>▶ Network Appliance N</li></ul>	<ul style="list-style-type: none"><li>▶ HCNP</li><li>▶ IFPUG Certifications</li><li>▶ dotMobi Certification</li><li>▶ SCMA</li><li>▶ MCSD</li><li>▶ NCLP</li><li>▶ XMLMaster Certificat</li><li>▶ CS5</li><li>▶ CHA</li></ul>	<ul style="list-style-type: none"><li>▶ ISEB</li><li>▶ ASTQB</li><li>▶ Aruba</li><li>▶ Data Center Universit</li><li>▶ HRCI</li><li>▶ CIW</li><li>▶ Patchlink</li><li>▶ International Consorti</li><li>▶ Acme-Packet</li></ul>	<ul style="list-style-type: none"><li>▶ Fortinet</li><li>▶ Ericsson</li><li>▶ Liferay</li><li>▶ Novell</li><li>▶ Huawei</li><li>▶ RSA</li><li>▶ MYSQL</li><li>▶ ISM</li><li>▶ CheckPoint</li></ul>

<http://www.pdfbraindumps.com>

Latest pdf braindumps provider, high pass rate

**Exam :** 000-175

**Title :** IBM WebSphere Lombardi Edition  
V7.2, Development (Entry)

**Vendors :** IBM

**Version :** DEMO

1. What is the correct JavaScript syntax to initialize a local variable named contact of a complex type Contact?

- A. `contact = new Contact();`
- B. `tw.local.contact = new Contact();`
- C. `tw.local.contact = new tw.local.Contact();`
- D. `tw.local.contact = new tw.object.Contact();`

**Answer: D**

2. The service "Get Request ID" needs to know the number of existing requests of a particular type in order to generate an ID for the request. It uses a nested service named "Get Request Count" for this purpose. What can be determined about data mapping?

- A. The type of the request is an output variable of the 'Get Request ID' service.
- B. The unique ID for the request is an input variable to the 'Get Request ID' service.
- C. The number of existing requests of a particular type is an input variable to the 'Get Request Count' service.
- D. The 'Get Request ID' service has a private variable that maps to the output from 'Get Request Count' service.

**Answer: D**

3. An application has five pieces of data: `creditScore`, `newHomeAddress`, `amountToBorrow`, `creditApproved`, and `appraisalPassed`. The data is organized in a complex variable, `loanApp`. How should the developer reference the credit score?

- A. `tw.local.creditScore`
- B. `tw.loanApp.creditScore`
- C. `tw.local.loanApp.creditScore`
- D. `tw.local.approveCredit.loanApp.creditScore`

**Answer: C**

4. A bank has a home loan process containing an 'Approve Credit' activity with a service attached with the same name. During the activity 'Approve Credit', a credit check is done and credit approval is based on the amount to be borrowed and the borrower's credit score. The loan application has five pieces of data: creditScore, newHomeAddress, amountToBorrow, creditApproved, and appraisalPassed. The data is organized in a complex variable, loanApp. What is the minimum output from the 'Approve Credit' service?

- A. loanApp
- B. creditApproved
- C. appraisalPassed
- D. amountToBorrow

**Answer: B**

5. What is the default visibility property for all new controls?

- A. Hidden
- B. Editable
- C. Disabled
- D. Required

**Answer: B**

6. A developer needs to build the Coach shown in the following Exhibit.

The image shows a web form for a 'Coach'. On the left is a profile picture placeholder labeled 'Coach'. The main form area has a title 'Lombardi Coach' and a sub-section 'Contact'. This sub-section is divided into two columns: 'Personal Information' and 'Contact Details'. The 'Personal Information' column contains 'Name:' and 'Birth Date:' labels with corresponding input fields. The 'Contact Details' column contains 'Phone:', 'Mobile:', and 'Email:' labels with corresponding input fields. A 'Submit' button is located at the bottom right of the form.

What is the minimum number of sections the developer needs to create in the Coach?

- A. 1
- B. 2
- C. 3
- D. 4

**Answer: D**

7. For each section on a Coach, there is an HTML table generated in the background. How are table rows dynamically defined or allocated? Based on the:

- A. number of sections on the Coach.
- B. number of Controls added to each section.
- C. entry specified on the customization property.
- D. Table Override property in the Presentation category.

**Answer: B**

8. A developer was asked to create a Coach based on the company's form for processing a new employee. For a copy of the company's form, refer to the Exhibit below.



9. An activity is defined as a conditional activity, and a script that returns a Boolean is written in the text box in the Condition tab. What will happen if the script returns true?

- A. The activity will be skipped.
- B. The activity will be performed.
- C. The activity will be performed if it is added to `tw.system.process.selectedConditionalActivities`.
- D. The activity will be skipped even if the activity is added to `tw.system.process.selectedConditionalActivities`.

**Answer: B**

10. To add a custom Coach XSL transformation to artifacts in a process application, the XSL file should be added as:

- A. a managed file.
- B. a localization resource.
- C. an installation service.
- D. process application settings.

**Answer: A**