

PDFBraindumps



Latest Pdf Braindumps	Top Certifications	Top Vendors		
<ul style="list-style-type: none">▶ LRP-614▶ BCABA▶ JN0-740▶ 250-405▶ DS-200▶ SDM_2002001040▶ ST0-250▶ H12-221▶ M2180-716	<ul style="list-style-type: none">▶ ISEB Certification▶ OCE▶ NVIDIA Certifications▶ Network+▶ IBM Certified Integrat▶ CCDH▶ IBM Certified Advanc▶ eserver Certified Spe▶ SAP-Certifications▶ Network Appliance N	<ul style="list-style-type: none">▶ HCNP▶ IFPUG Certifications▶ dotMobi Certification▶ SCMA▶ MCSD▶ NCLP▶ XMLMaster Certificat▶ CS5▶ CHA	<ul style="list-style-type: none">▶ ISEB▶ ASTQB▶ Aruba▶ Data Center Universit▶ HRCI▶ CIW▶ Patchlink▶ International Consorti▶ Acme-Packet	<ul style="list-style-type: none">▶ Fortinet▶ Ericsson▶ Liferay▶ Novell▶ Huawei▶ RSA▶ MYSQL▶ ISM▶ CheckPoint

<http://www.pdfbraindumps.com>

Latest pdf braindumps provider, high pass rate

Exam : **C2180-404**

Title : IBM Integration Bus V9.0,
Solution Development

Vendor : IBM

Version : DEMO

NO.1 A solution developer needs to validate an XML message in an MQInput node before doing any other bitstream parsing in subsequent nodes. The solution developer has enabled validation on content.

What additional node property configurations will allow the developer to accomplish this task?

- A. Advanced: Convert
- B. Parser Options: Parse Timing: Complete
- C. Parser Options: Parse Timing: Immediate
- D. Parser Options: Parse Timing: On Demand
- E. Input Message Parsing: Message format and Message Domain

Answer: E

NO.2 A solution developer is defining a DFDL model for a file that defines a purchase order. A field in the header, ItemCount, defines the number of purchase order items contained in the purchase order. The schema model is defined as shown below.

Name	Type	Min Occurs	Max Occurs
• PurchaseOrders			
— sequence		1	1
• Header		1	1
— sequence		1	1
• Description	string	1	1
• ItemCount	integer	1	1
• Items		1	unbounded
— sequence		1	1
• ItemName	string	1	1
• ItemDescription	string	1	1
• Quantity	integer	1	1
• UnitPrice	decimal	1	1

What modification must the developer make to the model to ensure that the number of items in the purchase order is equal to the value in ItemCount?

- A. Set theOccursCountKindproperty toImplicit.
- B. Add an Assert toItemsthat tests that items is less than or equal toItemCount.
- C. Add a variable instance to thesequenceelement that counts the number ofItemsrecords.
- D. Set theOccursCountKindproperty forItemstoExpressionand set the expression to{../Header/ItemCount}.

Answer: A

NO.3 A solution developer needs to create a broker archive to deploy an application on an integration server. During this process, the solution developer can add a flow as a .mgsflow or .cmf file. The solution developer decides to use .mgsflow.

Which node is allowed in the flow?

- A. A user-defined node that is created from a subflow.
- B. A user-defined node that is created from a Java implementation.
- C. A WebSphere Message Broker Version 7.0 Mapping node.

D. A subflow node that represents a subflow that is defined in a.msgflowfile.

Answer: A

Explanation:

Message flows that contain user-defined nodes that are created from subflows must be included in broker archive files as compiled message flow (.cmf) files.

Reference:https://www01.ibm.com/support/knowledgecenter/SSMKHH_9.0.0/com.ibm.etools.mft.doc/bs68460_.htm

NO.4 When using the IBM built-in node to output a file using WebSphere MQ Managed File Transfer, which message tree must be used to override the node properties?

A. Environment.Destination.File

B. Environment.Destination.FTE

C. LocalEnvironment.Destination.FTE

D. LocalEnvironment.WrittenDestination.FTE

Answer: D

Explanation:

LocalEnvironment.WrittenDestination.FTE message tree. You can override the Destination agent, Destination queue manager, Job name,

Reference:https://www01.ibm.com/support/knowledgecenter/SSMKHH_9.0.0/com.ibm.etools.mft.doc/bc34030_.htm

NO.5 A company needs to implement a generic gateway application which accepts COBOL input messages using WebSphere MQ transport. The first 15 bytes of each input message represents a common header for all messages. The 15 bytes header is used to determine the message type, length and routing information.

Which domain parser should the solution developer set in the input node to accomplish this?

A. MIME

B. BLOB

C. JSON

D. DataObject

Answer: B