

PDFBraindumps



Latest Pdf Braindumps	Top Certifications	Top Vendors		
<ul style="list-style-type: none">▶ LRP-614▶ BCABA▶ JN0-740▶ 250-405▶ DS-200▶ SDM_2002001040▶ ST0-250▶ H12-221▶ M2180-716	<ul style="list-style-type: none">▶ ISEB Certification▶ OCE▶ NVIDIA Certifications▶ Network+▶ IBM Certified Integrat▶ CCDH▶ IBM Certified Advanc▶ eserver Certified Spe▶ SAP-Certifications▶ Network Appliance N	<ul style="list-style-type: none">▶ HCNP▶ IFPUG Certifications▶ dotMobi Certification▶ SCMA▶ MCSD▶ NCLP▶ XMLMaster Certificat▶ CS5▶ CHA	<ul style="list-style-type: none">▶ ISEB▶ ASTQB▶ Aruba▶ Data Center Universit▶ HRCI▶ CIW▶ Patchlink▶ International Consorti▶ Acme-Packet	<ul style="list-style-type: none">▶ Fortinet▶ Ericsson▶ Liferay▶ Novell▶ Huawei▶ RSA▶ MYSQL▶ ISM▶ CheckPoint

<http://www.pdfbraindumps.com>

Latest pdf braindumps provider, high pass rate

Exam : **H12-223**

Title : Huawei Certified Network
Professional-R&S-IEEP

Vendor : Huawei

Version : DEMO

NO.1 Which of the following aspects should be considered during preliminary analysis of a migration project?

(Multiple Choice)

- A. Necessity
- B. Risks
- C. Costs
- D. Feasibility

Answer: A,B,D

NO.2 Which of the following scenarios is a loop test applicable to?

- A. To test whether a physical link is disconnected
- B. To test whether a switch can prevent loops and broadcast
- C. To test whether applications are properly connected
- D. To test whether a routing protocol can prevent loops

Answer: A

NO.3 Which of the following operations is unnecessary to resolve a failure for hosts in the same VLAN to communicate with each other?

- A. Run the display current-configuration command to check the PCB version and the software version of a card.
- B. Run the display interface interface-type interface-number command in any view to check the status of communication interfaces.
- C. Run the display vlan vlan-id command in any view to check whether the VLAN for communication interfaces has been created.
- D. Run the display mac-address command on the switch to check MAC address entries including the MAC address, port number, and VLAN ID.

Answer: A

NO.4 If a fault cannot be rectified in a short time on a complex network but the customer needs to restore network availability immediately, which of the following actions is recommended?

- A. Attempt to rectify the fault. If the fault cannot be rectified after a period of time, communicate with the customer.
- B. Tell the customer that this is impossible.
- C. Set up an alternative network environment.
- D. Communicate with the customer on skipping the faulty node, and set up an alternative network environment.

Answer: D

NO.5 Which of the following network features is described by counters such as mean time between failures (MTBF) and mean time to repair (MTTR)?

- A. Cost-effectiveness
- B. Availability
- C. Security

D. Scalability

Answer: B

NO.6 Current enterprise networks usually use OSPF as the routing protocol. What precautions are there when OSPF is used? (Multiple Choice)

- A. Determine that the backbone area will not split.
- B. Check whether secondary optimal routes exist on the network according to OSPF route selection rules.
- C. Check the OSPF network topology and ensure that no loop exists when OSPF routes are being calculated.
- D. Check whether all non-backbone areas are correctly and reliably connected to the backbone area.
- E. Verify that OSPF costs can correctly demonstrate the actual bandwidth of links at more than 100 Mbit/s.

Answer: A,B,D,E

NO.7 During follow-up operations of the structured network troubleshooting process, which of the following documents need to be transferred? (Multiple Choice)

- A. Troubleshooting intermediate documents
- B. User communication plan
- C. Troubleshooting summary report
- D. Change backup and maintenance suggestions

Answer: A,C,D

NO.8 Which of the following networks are involved during construction of a large enterprise network? (Multiple Choice)

- A. Storage network
- B. Transport network
- C. Data center network
- D. Wireless network
- E. Backbone network

Answer: C,D,E

NO.9 During the structured network troubleshooting process, which of the following items require attention in the information collection phase? (Multiple Choice)

- A. How to collect information
- B. What information to collect
- C. Risks in the information collection phase
- D. Whether authorization is required

Answer: A,B,C,D

NO.10 To rectify a VRRP group two-master fault, run the display this command on VLANIF interfaces on both ends of the VRRP group. Which of the following operations is not performed?

- A. Check whether the virtual IP address is the same on the VLANIF interfaces in the VRRP group.

- B. Check whether the interface IP addresses are on the same network segment.
- C. Check whether the VLANIF interfaces have the same VRRP group ID.
- D. You do not need to check whether the interval for sending VRRP Advertisement packets is the same on the VLANIF interfaces.

Answer: D

NO.11 Which of the following are possible causes for an MSTP failure in a LAN? (Multiple Choice)

- A. A physical link alternates between Up and Down, triggering the device to send a large number of TC packets.
- B. MSTP is configured incorrectly.
- C. The priority of the port in the specified MSTE is not configured.
- D. The MSTP-enabled device receives MSTPTC packets that are transparently sent or from the client.

Answer: A,B,D

NO.12 As shown in the figure, all interfaces of the router have ospf enabled. Which one of the following descriptions is correct?

- A. R5 will generate Type3 LSA in area 1
- B. The Type3 LSA generated by R3 in area 0 contains 10.0.2.2/32 routing information
- C. The Type3 LSA generated by R4 in area 1 contains 10.0.2.2/32 routing information
- D. The Type3LSA generated by R6 in area 1 contains 10.0.2.2/32 routing information

Answer: C

NO.13 When a large number of IP phones and WLAN APs exist on a network, which of the following switches is used?

- A. Switches supporting STP edge ports
- B. Switches supporting PoE
- C. Switches supporting SACG
- D. Switches supporting QoS

Answer: B

NO.14 If a fault is located on a router that works in redundancy mode with another router, which of the following methods is the most appropriate for subsequent troubleshooting?

- A. Top-down
- B. Bottom-up
- C. Configuration comparison
- D. Service traffic path check

Answer: C

NO.15 Which of the following line interface types belongs to a different category from other interface types?

- A. SC interface
- B. FC interface
- C. LC interface

D. BNC interface

Answer: D